The Rio Grande Southern Railroad Company

PIERPONT FULLER, JR., Receiver

TIME-TABLE No. 6

TAKES EFFECT

Sunday, July 18, 1948

at 12:01 A. M.

Standard Time, 105th Meridian

Superseding Time-Table of Districts 1, 1-A and 2

For the exclusive guidance of Employes; not for the information of the Public

The Management reserves the right to vary from it at pleasure

PIERPONT FULLER, JR.
Receiver
Denver

R. R. BOUCHER
Superintendent
Durango, Colo.

C. W. GRAEBING Genl. Mgr. & Auditor Durango, Colo.

THE RIO GRANDE SOUTHERN RAILROAD COMPANY

FIRST CLASS FIRST CLASS			DISTRICT 1		Same	FIRST CLASS FIRST CLASS		
THE WAY	LLIZO	371	Miles from Ridgway	STATIONS Mil		Car Capacity Passing Tracks	372	TINST CLASS
		Leave Daily		JULY 18, 1948		Tracks	Arrive Daily	
	Monte	12 50 PM	- william	WY RIDGWAY TTCWD THTO ! *	66.2	Yard	12 40 PM	7.00
1		12 58	3.0	JAY8	63.2	7	12 25	With the second
		f 104	5.2	HAGEN	61.0	25	f 12 17	Section 1
		f 110	7.3	DETI	58.9	12	f 12 10	
	N. C. C.	f 1 18	9.6	VALLEY VIEW W	56.6	12	f 12 01	
		s 1 33	12.3	PEAK TOY	52.9	40	8 11 51 AM	
		f 1 40	16.1	LEOPARD CREEK	50.1	10	f 11 43	
Maria ar ar	1	1 50	18.9	WADE	47.3	3	11 36	
	12063	f 200	22.2	BROWN w	44.0	24	f 11 27	
Service State State	BAL I	s 215	26.6	PV PLACERVILLE DY	39.6	39	s 11 15	2000 E 100 E 1
		f 2 21	29.1	FALL CREEK	37.1		f 11 06	
	479	f 2 32	32.6	WILSON	33.6	20	f 10 57	
		2 47	36.4	5.2 BILK	29.8	7	10 40	1
		s 2 51	37.8	VANCE JCT. TO YO	28.4	Yard	s 10 35	
The second		f 3 02	41.3	AMES w	24.9	2	1 10 25	
		s 312	44.9	OPHIR TO	21.3		n 10 15	The second second
		f 318	46.7	MATTERHORN	19.5	4	f 10 06	
HAN	DAL	f 3 28	49.0	TROUT LAKE W	17.2	25	t 9.59	
	100	s 3 40	52.6	LIZARD HEAD TOY	13.6	22	s 9.50	
	Syst	f 346	55.7	GALLAGHER	10.5		1 938	
		f 401	60.3	COKE OVENS w	5.7	22	f 9 26	
1,000	11 10	s 4 22 PM	66.2	80 RICO DRTG*TWC1	0.1			_8.5
		Arrive Daily		(66.2)			8 9 10 AM	
1	of de Top	3.32 18.68	Sint us	Schedule Time Average Speed per Hour			3.30	

Eastward

Miles from Ridgway	222	DISTRICT 1-A STATIONS TIMETABLE No. 6 JULY 18, 1948		Miles from Telluride	Car Capacity Passing Tracks	
37.8	м	VANCE JCT.	TO TO	7.3	31	
38.6		ANDERSON		6.5	25	
41.8	in the last	KEYSTONE		3.3	16	
45.1	DO	TELLURIDE	D*TW	and the	Yard	
		(7.3)				
		Schedule Time Average Speed per Hour				

THE RIO GRANDE SOUTHERN RAILROAD COMPANY

FIRST CLASS FIRST CLASS		Miles	DISTRICT 2		Miles Ca	Car	FIRST CLASS		FIRST CLASS				
d ed or ends had	teal (to	371	from Ridgway		STATIONS TIME TABLE No. 6		from Durango	Capacity Passing Tracks	372				
AND THE RESERVE	NOT LIVE	Leave Daily		home.		48	100	SE OF	Tracks	Arrive Daily		100	
The last of the last of		4 30 PM	66.2	RO	RICC	D pt*re	CWYB	96.4	Yard	9 05 AM	ALIEN POLICE	Contraction by	W.C. No.
	DOMESTIC OF	4 43	70.2	1 1000	MONTEL 4.3	ORES	4	92.4	2	8 51			CHANNE
		f 4.57	74.5		KIN - 5.7	G		88.1	20	f 8 41			Pinte
THE RESERVE OF	1 1 1 1 1 1 1	f 514	80.2	1.55	BEAR CI	REEK		82.4	16	f 8 26		1	Sell Dir
		f 532	85.9		MULDO 4.3	OON	TO SHA	76.7	30	f 811			
	200	5 46	90.2	(ES 19)	RAYMO 6.1	OND		72.4	4	8 01			OT PAGE
	THE WAY	f 6 02	96.3		STAPLE 6.0	TON		66.3	30	1 747			1000
		Ar. 6 30 PM	102.3	Dj	DOLOF	RES	DWY	60.3	Yard	Lv. 7 30 AM			
	2 4 7 3 4		103.4		LOST CA	INON	1000	59.2	35	(A)			Control
	The same of the same	455	111.8	lo e e e e	GLENO 3.8	COE	Y	50.8	25	E sur a			1700
No. of the last of	The second		115.6		MILLW	OOD		47.0	32				
STEEL STEEL	W. N. T. C.		122.5	MX	MANO	cos	DIW	40.1	38	- W	III III III III III III III III III II	18811 6	1
	Brangarille		125.3		MENEI 3.9	FEE		37.3	5				
	Susanie V	AT LAND OF STREET	129.2		BRAYT	ON	9	33.4	3		Contract of	Willelis	000
egolitica de la companya della companya de la companya de la companya della companya della companya de la companya della compa	the little of	-	132.9	To James	GRAI 3.6	Y	7616 T	29.7	30				400
		10.00	136.5		KAN 4.8	E		26.1	15				
817		MAC NEW W	141.3		CIM 4.2	A		21.3	15				
		GIE	145.5	uf	HESPEI	RUS	w	17.1	11				125
			146.8		UTE J	CT.	YC	15.8	26		Little Hill		
IL UE	Charles of	Selection in the	150.5	THE YORK	DENE 3.7	BY		12.1	4				A STATE OF THE PARTY OF THE PAR
The same of the	(MINESTER)		154.2		PINE F	RIDGE		8.4	31				
	All Control		157.1		PORT 2.2	ER	1 5/2 ·	5.5	29				
	THE PERSON NAMED IN		159.3		FRANKLI 3.3	N JCT.		3.3	20				
R. I	V-1-	ALC: STATE	162.6	DX TG	DURAN		Tista	D&RGW	Yard				
			TERMINE STATE		(96.	()	27.15	1444	Property of the second	Will Have	BUTCHES	1111111	
			2.00 18.00	THE PARTY	The state of	TO COMPANY	O PURE	10000	100 TO 10	1.35 22.74			

SPEED TABLE

	Tim	e of Perform	nnce	Speed	Time of Performance			
Speed Per Hour	1/4 Mile	34 Mile	1 Mile	Per Hour	34Mile	14 Mile	1 Mile	
Miles 5 10 15 20 25 30	M. S. 3 00 1 30 1 00 0 45 0 36 0 30	M. S. 6 00 3 00 2 01 1 30 1 12 1 00	M, S, 12 00 6 00 4 00 3 00 2 24 2 00	Miles 35 40 45 50 55 60	M. S. 0 25 0 22 0 20 0 18 0 16 0 15	M. S. 0 51 0 45 0 40 0 36 0 32 0 30	M. S. 1 42 1 30 1 20 1 12 1 05 1 00	

Local Time Inspectors are Located as follows:

Lindholm's Jewelers	Durango
Busy Corner Pharmacy	Telluride

OPEN HOURS TELEGRAPH OFFICES

Stations	Daily Hours	Sunday Hours None
Ridgway	8:00 A to 5:00 P	9:00 A to 6:00 P
Placerville	9:00 A to 6:00 P	
Telluride	8:00 A to 5:00 P	8:00 A to 5:00 P
Rico	8:00 A to 5:00 P	8:00 A to 5:00 P
Dolores	8:00 A to 5:00 P	9:00 A to 5:00 P
Durango—R.G.S. Dispatcher	8:00 A to 5:00 P	8:00 A to 5:00 P

ADDITIONAL SIDINGS AND SPURS NOT SHOWN IN TIME-TABLE

LOCATIO	N	NAME OF THE PROPERTY OF THE PR	CAR	SWITCH
District	Mile	NAMES	NG	CONNEC- TIONS
1 • • • • • • • • • • • • •	43.9 60 64.7 38.2 106.7 118.9 160.5	Butterfly Timber Spur Winkfield Illium Smalley Long Brick Yard	8 25 3 8 6 3 3	West End West End East End East End East End West End West End

SPECIAL TIME-TABLE RULES

Superseding General Rules and Regulations which are Inconsistent Therewith

- 1. EASTWARD TRAINS ARE SUPERIOR TO WESTWARD TRAINS OF THE SAME CLASS.
 - 2. All trains will leave Vance Jct. without clearance card.
 - 3. TRAIN REGISTER BOOKS are located at:

Ridgway Rico
Placerville Dolores
Vance Jct. Mancos
Telluride Durango

3-A. Conductors will register number of their Helper Engines with their trains.

4. YARD LIMIT STATIONS:

Ridgway Rico
Peak Dolores
Placerville Glencoe
Vance Jct. Mancos
Ophir Franklin Jct.
Lizard Head Durango

5. On trains in either direction at Peak, Lizard Head, Millwood and Cima, and on eastward trains at Telluride members of the train crew must assist in looking over the air brakes, as well as the general condition of the train, and trainmen must try the hand brakes on all cars and know the condition of same before train leaves these stations, and on engines equipped with water brakes such brakes must be in good working order.

After brakes have been released, retainers must be turned up before trains leave any station on a descending grade where retainers are required to control speed. Particular attention must be devoted to all rods and brake connections, brake shoes and levers, key bolts and split keys, and to all draft gear.

- 6. In handling of freight trains down Keystone hill and east side of Peak, but one (1) car having non-air or inoperative air brakes will be permitted to descend in solid coal or ore trains, and not more than two (2) cars with non-air or inoperative air brakes in merchandise or mixed trains.
- 7. Persons accompanying live stock or other freight will be carried on any freight train handling such live stock or freight when holding proper transportation, and when permission to accompany same is covered by contract. Passengers on freight trains should be informed that cabooses will not be pulled up to platform to receive or deliver passengers or baggage. Employes holding passes will be carried on any freight train to and from points at which trains stop when passes are stamped: "Good on Freight Trains."
- 8. Trainmen must not uncouple cars on grades without first testing hand brakes and knowing they will hold. Cars placarded "Explosives" or "Inflammable" must not be cut off while in motion.
- 9. All employes are hereby notified that there are coal chutes, buildings, platforms and other structures, located on the main line and on sidings, also structures and platforms belonging to private corporations and persons located on industrial sidings and spurs, that WILL NOT CLEAR a man riding on the side or on the top of a car; and all employes must protect themselves from injury in passing such structures.

Also, that it is dangerous to stand erect upon cars, and especially cars of extraordinary height while passing through snow sheds at Lizard Head, and necessary precautions must be used by all employes to protect themselves from injury from overhead structures at said points while rights on too and sides of cars.

riding on top and sides of cars. 1RGS 52.6 Lizard Head

Snow Shed

Side and Overhead

10. The following signs indicate:

s-Regular Stop.

- f-Flag stop to receive or discharge passengers or freight.
- x-Conditional stop as shown under Rule 14.
- 1-Meals or lunch.
- N-Day and night telegraph office.
- NO-Night (only) telegraph office. D-Day (only) telegraph office.
- DN-Part day and part night telegraph office.
- TG-Telegraphone station.
- C-Coal station.

W-Water station.

Y-Wye.

T-Turntable.

§—Scale.

B-Bulletin.

‡-Standard clock.

*-San

- 11. The speed of trains should be so restricted that absolute safety will be assured, and the maximum speed will ordinarily be that necessary to make the schedule. Except in territory specified below enginemen and conductors may moderately increase the speed above that required by the schedules when the necessity arises, if, in their judgment it be safe and prudent, bearing in mind that safety in operation is to be given first consideration, and always giving due consideration to track and surrounding conditions. At no time, however, should a speed exceeding thirty-five miles per hour be made with narrow gauge passenger trains, nor a speed exceeding twenty-five miles per hour be made with narrow gauge mixed or freight trains.
- Speed restrictions governing freight trains will govern speed of light engines unless otherwise provided in Rule 11-B.
- 11-B. The specific restrictions shown below cover certain territories where conditions make a specific limited speed necessary, and these restrictions, also any other special speed restrictions, must be complied with.

	Mixed or
Passenger	Freight
M.P.H.	M.P.H.
R. G. S	25
Sharp Curves	15
2.50% to 3.00% grades20	15
4.00% grades	12
Mixed trains 2.50% to 3% grades	18
Mixed trains 4% grades	12
Over bridges between Matterhorn and Ames10	10
Durango Yard, Smelter High Line Switch 3	3
All Districts, except where specific restrictions in certain require lower speed:	territories

require lower speed:	
In or out of turnouts15	15
Over railroad crossings, not interlocked25	20
Engines backing up	15
Trains handling dead engines with side rods up	25
Dead engines with side rods all down	15
Dead engines with one pair wheels swinging	10
Steam derricks	25

- City ordinance speed limits as follows: Placerville 6 miles per hour.
- 13. Company Surgeons are located as follows:

	on geon, benter
A. L. BURNETTDurango	SABIN MINERTelluride
O D DYNAMAN	
O. B. RENSCHDurango	E. G. MERRITT Dolores
YE Y CAN LAYOUT YOU	
E. L. SPANGLEROuray	J. L. TROTTERMancos
	Mark the second state of t

- 13-A. Hospitals are located as follows: Durango, "Mercy", Salida, "D. & R. G. W."
- 13-B. PROMPT REPORT MUST BE MADE OF ALL ACCIDENTS. Personal injuries, when train is not wrecked, by message to Superintendent, who will promptly advise Assistant to Receiver. Telegraph Accident Report (Form 3884) must be made at once as per instructions thereon. Mail reports of all accidents and casualties must be promptly made, using the following forms, according to the instructions thereon and in the Book of Rules:

Personal Injury Report (Form 3922).
Accident Report (Form 1216).
Personal Injury Card (Form 1217).
Ejectment (Form 3926).
Inspection (Form 4012).
Fire Report (Form (4119).
Stock Report (Enginemen—Form 3511).
Stock Report (Sectionmen—Form 4117).

13-C. SURGICAL ATTENTION. (Passengers and employes.) Whenever passengers or employes are injured, everything must be done to care for them properly, either calling the Company's nearest Surgeon to treat them (and if seriously injured, calling the nearest competent Surgeon to be had, until the Company's Surgeon can get to the place of accident), or if they are able to be moved, taking them to the nearest place at which the Company has a Surgeon and turning them over to him for care and treatment. If other than a Company Surgeon is called, he is to be advised that he is called for first attention only, beyond which the Company assumes no responsibility for his bill.

(Others). When persons not employes or passengers (for example, persons injured at crossings, trespassers, outsiders at work around depots or other industries, etc.) are injured, if they are unable to care for themselves, and if no friends or others are at hand to care for them, the nearest Company Surgeon should be called, or if he cannot be reached, the nearest other competent Surgeon, which Surgeon must be advised that he is called for emergency attention only and that the Company does not assume responsibility for his bill. If trespassers are not taken charge of by friends or others, they should be turned over to the public authorities as soon as possible, and no expense incurred in behalf of the Company except the emergency attention above noted.

13-D. Parties calling Surgeons should explain fully as possible the nature of the injuries so that the Surgeon may know what equipment to bring with him.

13-E. When any wreck, collision of trains, or any collision of trains with vehicles or pedestrians, resulting in loss of life or injury to persons in Colorado, the superior officer, agent or employe on the ground at the time of such accident shall immediately notify the Public Utilities Commission, Capitol Building, Denver, Colorado, by telegram, the details of such accident, stating the immediate location and the nature of the accident and the number of persons killed or injured.

Information covering such accidents must be sent by Western Union Telegraph Company wires, and all Agents will accept and so transmit same, assessing charges therefor against the Railroad Account.

 Noel, M. P. 14.6 and Vanadium, M. P. 33.0, Flag stops Nos. 371 and 372.

15. The following are auxiliary lines (Rules 14-T, 14-U). Vance Jct., District 1-A.

The following special instructions, Rules 18 and 25 inclusive, in connection with the Rules and Regulations of the Operating Department, 1924, supersede all previous rules and instructions inconsistent therewith:

16. Rule 11 is revised as follows:

"A train finding a fusee burning on or near its track must stop and wait until it has burned out before proceeding at restricted speed for a distance of at least one-half mile, or in Automatic Block Signal territory, to the next Automatic Block Signal. 17. Rule 92 is revised as follows:

"A train must not leave a station in advance of its schedule leaving ime."

18. Second paragraph of Rule 104-E is revised as follows:

"A train taking a siding must not be stopped for a Trainman to close the switch, nor may the switch be closed, until the train is entirely clear of main track."

19. Add Rule 220-B as follows:

"Train orders and MB'S relating to track conditions, unless annulled, must be respected by conductors and enginemen on all trips made during the tour of duty on which such orders are received."

20. First paragraph of Rule 221 is amended to read:

"Except at stations where all trains are required to obtain a clearance card, a fixed signal must be used at each train order office, which shall indicate 'stop' when there is an operator on duty, except when changed to indicate 'proceed' to allow a train to pass when there are no train orders for any train in the same direction. Where other than two-position or three-position semaphore is used, the signal must not be changed to indicate 'proceed' when there is a train order for a train in either direction. A train must not pass the signal while 'stop' is indicated, without a clearance card. The signal must be returned to indicate 'stop' as soon as a train has passed. It must be fastened at 'proceed' only when no operator is on duty."

21. Add to instructions following Example 3 of Form G: "Work extras, whether required to protect or not protect against extra trains, must clear the time of the extra five minutes."

22. Add to instructions following form K:

"It will be necessary to obtain the annulment of a schedule or section but once, provided conductor and engineman have a copy in their possession on each trip."

23. Rule 86, Rules and Regulations of the Operating Department, 1924, does not apply to Narrow Gauge Lines. In Narrow Gauge territory an inferior train must clear the time of a superior train, in the same direction, not less than five minutes.

24. In making back up movements over street crossings in yards a Trainman must ride on rear footboard or rear step of engine, except where Crossing Flagman is on duty.

 K27 class engs. must not exceed six miles per hour over East switch at Bear Creek.

ADJUSTED TONNAGE RATINGS

FROM	то	Class of Engine K-27 No. of Engines 450-464	Class of Engine C-25 No. of Engines 375	Class of Engine C-21 No. of Engines 360, 361	Class of Engine T-19 No. of Engines RGS 20 22, 25	Class of Engine C-17 C-18 No. of Engines 300-306 315-320	Class of Engine C-19 No. of Engines 340-349 RGS 40, 41, 42	Class of Engine C-16 No. of Engines 200-286 RGS 3-17	Class of Engine T-12 No. of Engines 166-177	Adjust- ment Factor
		Tons	Tons	Tons	Tons	Tons	Tons	Tons	Tons	Tons
Ridgway	Peak	183	173	113	115	106	92	79	67	1
Placerville	Peak	275	250	175	175	160	140	120	110	2
Placerville	Vance Jet.	430	400	290	285	260	230	210	185	3
Vance Jet	Telluride	183	173	113	115	106	92	79	67	1
Vance Jet.	Lizard Head	250	230	160	160	145	130	105	100	2
Rico	Lizard Head	275	250	175	175	160	140	120	110	2
Dolores	Rico	490	SERVING N		310	280	250	220	205	3
Dolores	Glencoe	520			325	295	265	235	210	3
Glencoe	Millwood	360		La Series II	230	210	185	160	145	3
Mancos	Millwood	360			230	210	185	160	145	3
Mancos	Cima	360			230	210	185	100	145	3
Durango	Cima	360			230	210	185	160	145	3

These ratings are the usual tonnage ratings for dead Freight trains. Chief dispatchers are authorized to increase or decrease these ratings in their discretion in accordance with standing instructions, to adjust for slack grades, conditions of power, necessity for maintaining stock schedules, or for any other reasons which justify.

In computing tonnage, the adjustment factor represents the number of tons which shall be added to the total weight of each car, loaded or empty. The caboose shall count as a car. Tonnage hauled may exceed the rating by a fraction of a car.

On 4% grades, engines equipped with 1-9½" Compressor 30 Cars 575 Tons
1-11" Compressor 45 Cars 650 Tons
2-9½" Compressor 60 Cars 800 Tons
When equipped with one 8½" C. C. air Compressor,

35 cars coal or other heavy loading 45 cars stock and other light loading 1150 tons 1150 tons 45 cars mixed loads and empties

60 cars empties

1150 tons 1150 tons